



## CA CONTROLLED ACCESS, INC. Turnstiles and ADA Gates

### The Brute™ BR5500-P

Portable | Interior & Exterior Application

#### We're the #1 Choice of Top Architects, Security Pros and Engineers

For more than 30 years, Controlled Access has been the globally trusted name in pedestrian control equipment. Made in Ohio and shipped worldwide, we are the first choice of leading architects, facility managers, security consultants, and engineers. Whether your project requires high security full-height turnstiles, waist high units, or matching ADA accessible gates, Controlled Access is the secure choice. We're experienced in access control systems, from card readers to biometric scanning, to give you the power to control access.

The Brute™ Series units operate reliably with high traffic volume areas where cost is an important consideration. Heavy 7-gauge carbon steel cabinets can be interfaced with optional LCD counters, card readers, push button, and wireless remotes. Standard powder coat colors are shown below. Custom colors are available and can be quoted upon request. Our matching tripod style unit is the BR5500-S. We also offer two ADA compliant handicap gates with this series (BR5000-ADA and BR5000-ADA-P; portable)

#### About Controlled Access:

Controlled Access manufactures the most reliable full-height turnstiles available. The High-Security Series units can be engineered to meet all your security and control requirements, and can be created as stand-alone units, or as part of an integrated system. Available in stainless steel (304 or 316), carbon steel with powder coating, or hot-dipped galvanized finish. These units can be fitted for any application with leading edge technology and features.

# The Brute BR5500-P Series

Portable | Waist High Turnstile | Interior & Exterior Application

## Applications:

This portable turnstile is made for years of reliable service (and offers many options) where cost is an important consideration. It is ideal for public venues such as convention halls, fairs, amusement parks and cafeterias.

## Product Features:

### Materials & Finishes:

- Lid: Our signature 304 stainless steel / No. 4 satin finish
- Cabinet: Your choice of 8 designer powder coat colors to match any décor. Black is standard. Custom RAL colors can be quoted.

## Design & Construction:

- Designed for secure and reliable operation with aesthetics in mind
- Cabinet is constructed with rigid (7 gauge) carbon steel
- Cover is constructed with (16 gauge) 304 stainless steel, No. 4 satin finish
- Arm assembly constructed with 1 5/16" (33.4mm) diameter, (12 gauge) stainless steel
- Hub 4 1/2" (114.3mm) o.d. also made from stainless steel


## Dimensions:

- **Height:** 37" (939.8mm)
- **Width:** 32.750" (831.8mm)
- **Depth:** 20.125" (511.2mm)
- **Passage:** 18.5" (469.9mm)

\* Dimensions are subject to change without notice



Optional battery back-up available



## Operation Features

### 6500 Series Control Head:

- Auto-indexing (self-centering) with adjustable hydraulic shock suppression
- Hardened tool steel locking bars, cam and roller assemblies
- Permanently lubricated bearings
- Your choice of manual or electronic control on both directions
- Nearly universal integration to any number of access control systems
- Your choice on each electronic direction of locking or unlocking on power failure

## Options:

- Daylight visible indicator lights
- Bi-directional key overrides
- 8 digit key resettable LCD counter with seven year lithium battery
- 12 Ah battery back-up system (2x 12VDC batteries) with 2 amp 24VDC charger with base cover
- Additional options available upon request

## Warranty:

Units are warranted against defects in materials and workmanship for a period of one year from date of delivery. See warranty information for specific details.

## Electrical Specifications:

Input Voltage: 100-240 VAC  
 Input Current: 1.3 - .55 A  
 Frequency: 50/60 Hz  
 Storage Temperature: -40 to 158°F  
 Operating Temperature: -4 to 131°F  
 Operating Voltage: 24VDC  
 Operating Current: 1.2 A (typical)

## Electrical Specifications:

Austenitic stainless steel:  
 ASTM A240, A249, A276

Hot rolled steel:  
 AISI C-1020, AISI C-1018

All fasteners provided meet IFI ANSI/ASME Fastener Standards

American Welding Society (AWS) Standard D 1.1



The 6500 Series Control Head is certified to conform to the following standards:  
 UL 294, UL 325, UL Subject 2593,,  
 4008027 CAN/ULC s319 & CSA  
 C22.2#247



Controlled Access Inc. is certified by Advantage International Registrar to be an ISO 9001:2015 company

